



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT100ES06	100,000	H10006	STS 630	Ø2.4

- Note  
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/22	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	-	-
3	COLLAR	100,000PSI 3/8"	FA100RS06	STS 630	2	EA	-
2	GLAND	100,000PSI 3/8"	FA100GS06	STS 316CW	2	EA	-
1	ELBOW	100,000PSI 3/8"	FT100ES06	STS 630	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT			
General tolerance is given in KS B ISO 2768-1				ULTRA HIGH PRESSURE FITTING			
NORMINAL DIM.(MM)		CLASS OF FINISH		TITLE			
OVER	UNDER	TOL.		100,000PSIG 3/8" ELBOW			
0.5	6	±0.1	✓ = 200S, ~	FT100ES06			
6	30	±0.2	W = 12.5, ▽	APPD BY: CHD BY: DED BY: DRN BY: WORK NO. HI-KYJ-200822-10 REV. NO.			
30	120	±0.3	X = 50S, ▽	SCALE: DRN DATE: DWG NO. FT100ES06			
120	315	±0.5	Y = 12.5S, ▽				
315	1000	±0.8	Z = 3.2S, ▽				
1000	2000	±1.2	Z = 0.8S, ▽				
	OVER 2000	±1.5					