



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT150CS06	150,000	H15006	STS 630	Ø2.4

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/26	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	150,000PSI 3/8"	FA150RS06	STS 630	4	EA	-
2	GLAND	150,000PSI 3/8"	FA150GS06	STS 316CW	4	EA	-
1	CROSS	150,000PSI 3/8"	FT150CS06	STS 630	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT			
General tolerance is given in KS B ISO 2768-1				ULTRA HIGH PRESSURE FITTING			
NORMINAL DIM.(MM)				TITLE			
		CLASS OF FINISH		150,000PSIG 3/8" CROSS			
OVER	UNDER	TOL.	✓ = 200S, ~	FT150CS06			
0.5	6	±0.1	W = 125, ▽	APPD BY			
6	30	±0.2	X = 125, ▽	CHD BY			
30	120	±0.3	Y = 125, ▽	DED BY			
120	315	±0.5	Z = 125, ▽	DRN BY			
315	1000	±0.8	▽ = 3.2S, ▽	WORK NO.			
1000	2000	±1.2	▽ = 0.8S, ▽	HI-KYJ-200228-03			
OVER 2000		±1.5		SCALE			
				DRN DATE			
				DWG NO.			
				FT150CS06			
			HIFLUX ®				