



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT150ES06	150,000	H15006	STS 630	Ø2.4

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/26	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	150,000PSI 3/8"	FA150RS06	STS 630	2	EA	-
2	GLAND	150,000PSI 3/8"	FA150GS06	STS 316CW	2	EA	-
1	ELBOW	150,000PSI 3/8"	FT150ES06	STS 630	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT ULTRA HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1				TITLE 150,000PSIG 3/8" ELBOW			
NORMINAL DIM.(MM)		CLASS OF FINISH		DRAWING NO. FT150ES06			
OVER	UNDER	TOL.	✓ = 20S, ~	APPD BY	CHD BY	DED BY	DRN BY
0.5	6	±0.1	W = 12S, ▽	K.Y.J	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	X = 12S, ▽	SCALE		DRN DATE	WORK NO. HI-KYJ-200228-01
30	120	±0.3	Y = 12S, ▽	DWG NO.		FT150ES06	REV. NO.
120	315	±0.5	Z = 12S, ▽	HIFLUX			
315	1000	±0.8	AA = 12S, ▽				
1000	2000	±1.2	AB = 12S, ▽				
	OVER 2000	±1.5	AC = 12S, ▽				