



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT150TS06	150,000	H15006	STS 630	Ø2.4

- Note
1. All dimensions for reference only and subject to change.

REV NO.	DESCRIPTION	FOR APPROVAL	DRAWING	REVIEWED BY	APPROVED BY
0		FOR APPROVAL			
		09/26	K.Y.J		
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	150,000PSI 3/8"	FA150RS06	STS 630	3	EA	-
2	GLAND	150,000PSI 3/8"	FA150GS06	STS 316CW	3	EA	-
1	TEE	150,000PSI 3/8"	FT150TS06	STS 630	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT: ULTRA HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1				TITLE: 150,000PSIG 3/8" TEE			
NORMINAL DIM.(MM)				PART NO.: FT150TS06			
OVER	UNDER	TOL.	CLASS OF FINISH				
0.5	6	±0.1	✓ = Ra, 200S, ~				
6	30	±0.2	W = Rz, 125, 50S, ~				
30	120	±0.3	X = Rz, 12.5S, ~				
120	315	±0.5	Y = Rz, 3.2S, ~				
315	1000	±0.8	Z = Rz, 0.8S, ~				
1000	2000	±1.2					
	OVER 2000	±1.5					
APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.		
	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200208-02	0		
SCALE		DRN DATE		DWG NO.		FT150TS06	
				HIFLUX ®			