



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20CS06	20,000	H2006	STS 316CW	Ø5.2

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	EA	-
3	COLLAR	20,000psi 3/8"	FA20RS06	STS 316CW	4	EA	-
2	GLAND	20,000psi 3/8"	FA20GS06	STS 316CW	4	EA	-
1	CROSS	20,000psi 3/8"	FT20CS06	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT MEDIUM PRESSURE FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1					TITLE 20,000PSI 3/8" CROSS		
NORMINAL DIM.(MM)			CLASS OF FINISH		FT20CS06		
OVER	UNDER	TOL	√ = R	200S,	APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = R	50S,	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	√ = R	12.5S,	DRN BY	WORK NO.	HE-KYJ-200625-01
30	120	±0.3	√ = R	3.2S,	K.Y.J	DWG NO.	FT20CS06
120	315	±0.5	√ = R	0.8S,	SCALE	DRN DATE	
315	1000	±0.8	√ = R				
1000	2000	±1.2	√ = R				
OVER 2000		±1.5	√ = R				
				HIFLUX ®			