



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT20CS09	20,000	H2009	STS 316CW	Ø7.9

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	09/22	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	-	-
3	COLLAR	20,000PSI 9/16"	FA20RS09	STS 316CW	4	EA	-
2	GLAND	20,000PSI 9/16"	FA20GS09	STS 316CW	4	EA	-
1	CROSS	20,000PSI 9/16"	FT20CS09	STS 316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT MEDIUM PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1				TITLE 20,000PSIG 9/16" CROSS			
NORMINAL DIM.(MM)		CLASS OF FINISH		FT20CS09			
OVER	UNDER	TOL	√ = Ra, 200S,	APPD BY			
0.5	6	±0.1	√ = Ra, 50S,	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	√ = Ra, 12.5S,	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-220823-04
30	120	±0.3	√ = Ra, 3.2S,	SCALE		DRN DATE	DWG NO.
120	315	±0.5	√ = Ra, 0.8S,	FT20CS09		FT20CS09	REV. NO.
315	1000	±0.8		<b>HIFLUX</b> ®			
1000	2000	±1.2					
OVER 2000		±1.5					