



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT20CS12	20,000	H2012	STS 316CW	Ø11.1

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	07/17	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
		DESIGN SECTION			

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	20,000PSI 3/4"	FA20RS12	STS 316CW	4	EA	-
2	GLAND	20,000PSI 3/4"	FA20GS12	STS 316CW	4	EA	-
1	CROSS	20,000PSI 3/4"	FT20CS12	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT MEDIUM PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1				TITLE 20,000PSIG 3/4" CROSS			
NOMINAL DIM.(MM)			CLASS OF FINISH	FT20CS12			
OVER	UNDER	TOL.	✓ = √, 200S, ~	APPD BY			
0.5	6	±0.1	∇ = ∇, 50S, ∇	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	∇ = ∇, 12.5S, ∇∇	K.Y.J	K.Y.J	K.Y.J	H-KYJ-230717-02
30	120	±0.3	∇ = ∇, 3.2S, ∇∇∇	SCALE	DRN DATE	DWG NO.	REV. NO.
120	315	±0.5	∇ = ∇, 0.8S, ∇∇∇∇			FT20CS12	
315	1000	±0.8		HIFLUX ®			
1000	2000	±1.2					
OVER 2000		±1.5					