



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20CS16	20,000	H2016	STS 316CW	Ø17.5

**- Note**

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	EA	-	
3	COLLAR	20,000psi 1"	FA20RS16	STS 316CW	4	EA	
2	GLAND	20,000psi 1"	FA20GS16	STS 316CW	4	EA	
1	CROSS	20,000psi 1"	FT20CS16	STS 316CW	1	EA	
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT MEDIUM PRESSURE FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1		CLASS OF FINISH		TITLE 20,000PSI 1" CROSS			
NORMINAL DIM.(MM)				FT20CS16			
OVER	UNDER	TOL.	✓ = 0/	▽ = 0.200S,	APPROD BY		
0.5	6	±0.1	▽ = 0.2/	▽ = 0.2/	DES BY	WORK NO.	REV. NO.
6	30	±0.2	▽ = 0.4/	▽ = 0.4/	K.Y.J	HI-KYJ-200625-01	
30	120	±0.3	▽ = 0.6/	▽ = 0.6/	DRN BY	DWG NO.	
120	315	±0.5	▽ = 0.8/	▽ = 0.8/	K.Y.J	FT20CS16	
315	1000	±0.8	▽ = 1.2/	▽ = 1.2/	SCALE	DRN DATE	
1000	2000	±1.2	▽ = 1.6/	▽ = 1.6/			
OVER 2000		±1.5	▽ = 2.0/	▽ = 2.0/			
				<b>HIFLUX</b> ®			