



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20ES04	20,000	H2004	STS 316CW	Ø2.8

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	EA	-	
3	COLLAR	20,000psi 1/4"	FA20RS04	STS 316CW	2	EA	
2	GLAND	20,000psi 1/4"	FA20GS04	STS 316CW	2	EA	
1	ELBOW	20,000psi 1/4"	FT20ES04	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE		DESCRIPTION		FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT MEDIUM PRESSURE FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1				TITLE 20,000PSI 1/4" ELBOW			
NORMINAL DIM.(MM)		CLASS OF FINISH		FT20ES04			
OVER	UNDER	TOL.	✓ = 20S, ~	APPD BY			
0.5	6	±0.1	✓ = 12S, ~	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	✓ = 12S, ~	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200717-01
30	120	±0.3	✓ = 12S, ~	SCALE		DRN DATE	DWG NO.
120	315	±0.5	✓ = 12S, ~				FT20ES04
315	1000	±0.8	✓ = 12S, ~				
1000	2000	±1.2	✓ = 12S, ~				
OVER 2000		±1.5	✓ = 12S, ~				