



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20ES12	20,000	H2012	STS 316CW	Ø11.1

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	EA	-	
3	COLLAR	20,000psi 3/4"	FA20RS12	STS 316CW	2	EA	
2	GLAND	20,000psi 3/4"	FA20GS12	STS 316CW	2	EA	
1	ELBOW	20,000psi 3/4"	FT20ES12	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE		DESCRIPTION		FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM	PROJECT MEDIUM PRESSURE FITTING BLOCK				
General tolerance is given in KS B ISO 2768-1			TITLE 20,000PSI 3/4" ELBOW				
NORMINAL DIM.(MM)			FT20ES12				
OVER	UNDER	TOL.	CLASS OF FINISH				
0.5	6	±0.1	✓ = 20S, ~				
6	30	±0.2	W = 12S, ▽				
30	120	±0.3	X = 12S, ▽				
120	315	±0.5	Y = 12S, ▽				
315	1000	±0.8	Z = 12S, ▽				
1000	2000	±1.2	Z = 12S, ▽				
	OVER 2000	±1.5	Z = 12S, ▽				
APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.		
	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-240820-12			
SCALE		DRN DATE	DWG NO.	REV. NO.			
			FT20ES12				
<b>HIFLUX</b> <sup>®</sup>							