



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20TS06	20,000	H2006	STS 316CW	Ø5.2

**- Note**

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	EA	-	
3	COLLAR	20,000psi 3/8"	FA20RS06	STS 316CW	3	EA	
2	GLAND	20,000psi 3/8"	FA20GS06	STS 316CW	3	EA	
1	TEE	20,000psi 3/8"	FT20TS06	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT MEDIUM PRESSURE FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1				TITLE 20,000PSI 3/8" TEE			
NORMINAL DIM.(MM)		CLASS OF FINISH		FT20TS06			
OVER	UNDER	TOL.	✓ = 20S, ~	APPD BY			
0.5	6	±0.1	✓ = 12S, ~	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	✓ = 12S, ~	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-20023-01
30	120	±0.3	✓ = 12S, ~	SCALE		DRN DATE	DWG NO.
120	315	±0.5	✓ = 12S, ~				FT20TS06
315	1000	±0.8	✓ = 12S, ~				
1000	2000	±1.2	✓ = 12S, ~				
OVER 2000		±1.5	✓ = 12S, ~				