



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	Orifice Size
FT20TS16	20,000	H2016	STS 316CW	Ø17.5

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	EA	-
3	COLLAR	20,000psi 1"	FA20RS16	STS 316CW	3	EA	-
2	GLAND	20,000psi 1"	FA20GS16	STS 316CW	3	EA	-
1	TEE	20,000psi 1"	FT20TS16	STS 316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT MEDIUM PRESSURE FITTING BLOCK				
General tolerance is given in KS B ISO 2768-1		PROJECT		TITLE			
NORMINAL DIM.(MM)		PROJECT		20,000PSI 1" TEE			
		PROJECT		FT20TS16			
OVER	UNDER	TOL	CLASS OF FINISH		APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = R, 200S,	~	K.Y.J	K.Y.J	DRN BY
6	30	±0.2	√ = R, 50S,	▽			WORK NO.
30	120	±0.3	√ = R, 12.5S,	▽▽			HI-KYJ-20025-01
120	315	±0.5	√ = R, 3.2S,	▽▽▽			REV. NO.
315	1000	±0.8	√ = R, 0.8S,	▽▽▽▽			
1000	2000	±1.2					
OVER 2000		±1.5					
			SCALE		DRN DATE	DWG NO.	FT20TS16
			HIFLUX ®				