



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT60CS04	60,000	H6004	STS 316CW	Ø2.4

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/24	K.Y.J		
	REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	60,000PSI 1/4"	FA60RS04	STS 316CW	4	EA	-
2	GLAND	60,000PSI 1/4"	FA60GS04	STS 316CW	4	EA	-
1	CROSS	60,000PSI 1/4"	FT60CS04	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT: HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1					TITLE: 60,000PSIG 1/4" CROSS		
NOMINAL DIM.(MM)			CLASS OF FINISH		FT60CS04		
OVER	UNDER	TOL.	$\sqrt{}$ = $\sqrt{}$, 200S,		APPD BY	CHD BY	DED BY
0.5	6	±0.1	$\sqrt{}$ = $\sqrt{}$, 50S,		K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	$\sqrt{}$ = $\sqrt{}$, 12.5S,		DRN BY	WORK NO.	REV. NO.
30	120	±0.3	$\sqrt{}$ = $\sqrt{}$, 3.2S,		K.Y.J	H-KYJ-200824-05	
120	315	±0.5	$\sqrt{}$ = $\sqrt{}$, 0.8S,		SCALE	DWG NO.	
315	1000	±0.8			DRN DATE	FT60CS04	
1000	2000	±1.2			HIFLUX ®		
OVER 2000		±1.5					