



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT60CS06	60,000	H6006	STS 316CW	Ø3.2

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/24	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	60,000PSI 3/8"	FA60RS06	STS 316CW	4	EA	-
2	GLAND	60,000PSI 3/8"	FA60GS06	STS 316CW	4	EA	-
1	CROSS	60,000PSI 3/8"	FT60CS06	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1					TITLE 60,000PSIG 3/8" CROSS		
NOMINAL DIM.(MM)			CLASS OF FINISH		FT60CS06		
OVER	UNDER	TOL.	√ = √	200S,	APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = √	50S,	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	√ = √	12.5S,	DRN BY	WORK NO.	REV. NO.
30	120	±0.3	√ = √	3.2S,	K.Y.J	H-KYJ-260624-02	
120	315	±0.5	√ = √	0.8S,	SCALE	DRW DATE	DWG NO.
315	1000	±0.8	√ = √				FT60CS06
1000	2000	±1.2	√ = √		HIFLUX ®		
OVER 2000		±1.5	√ = √				