



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT60CS09	60,000	H6009	STS 316CW	Ø4.8

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/24	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	-	-	-
3	COLLAR	60,000PSI 9/16"	FA60RS09	STS 316CW	4	EA	-
2	GLAND	60,000PSI 9/16"	FA60GS09	STS 316CW	4	EA	-
1	CROSS	60,000PSI 9/16"	FT60CS09	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1					TITLE 60,000PSIG 9/16" CROSS		
NORMINAL DIM.(MM)			CLASS OF FINISH		FT60CS09		
OVER	UNDER	TOL	√ = √	200S,	APPD BY	CHD BY	DED BY
0.5	6	±0.1	√ = √	50S,	K.Y.J	K.Y.J	DRN BY
6	30	±0.2	√ = √	12.5S,			K.Y.J
30	120	±0.3	√ = √	3.2S,			WORK NO.
120	315	±0.5	√ = √	0.8S,			HI-KYJ-260024-05
315	1000	±0.8	√ = √				REV. NO.
1000	2000	±1.2	√ = √				
OVER 2000		±1.5	√ = √				SCALE
					DRN DATE		DWG NO.
							FT60CS09