



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Port Type	Material	ORIFICE SIZE
FT60TS09	60,000	H6009	STS 316CW	Ø4.8

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	06/23	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	DESIGN SECTION

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	-	-	-
3	COLLAR	60,000PSI 9/16"	FA80RS09	STS 316CW	3	EA	-
2	GLAND	60,000PSI 9/16"	FA80GS09	STS 316CW	3	EA	-
1	TEE	60,000PSI 9/16"	FT60TS09	STS 316CW	1	EA	-
ITEM	NAME OF PART PART CODE	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°			UNIT: MM	PROJECT HIGH PRESSURE FITTING			
General tolerance is given in KS B ISO 2768-1					TITLE 60,000PSIG 9/16" TEE		
NOMINAL DIM.(MM)			CLASS OF FINISH		FT60TS09		
OVER	UNDER	TOL.	✓ = √	200S, ~	APPD BY	CHD BY	DED BY
0.5	6	±0.1	✓ = √	50S, ▽	K.Y.J	K.Y.J	DRN BY
6	30	±0.2	✓ = √	12.5S, ▽▽			K.Y.J
30	120	±0.3	✓ = √	3.2S, ▽▽▽	SCALE	DRN DATE	WORK NO.
120	315	±0.5	✓ = √	0.8S, ▽▽▽▽			HE-KYJ-200623-04
315	1000	±0.8					REV. NO.
1000	2000	±1.2					0
OVER 2000		±1.5					DWG NO.
							FT60TS09
				<b>HIFLUX</b> ®			