



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTNCS02	15,000	Ø2.4	1/8" NPT	STS 316CW

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com																													
4	-	-	-	-	EA																										
3	-	-	-	-	EA																										
2	-	-	-	-	EA																										
1	CROSS	1/8" NPT	FTNCS02	STS 316CW	1 EA																										
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK																								
	PART CODE		DESCRIPTION		FOR ONE SET																										
MATERIAL LIST FOR ONE SET																															
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT TAPER THREAD FITTING BLOCK																												
General tolerance is given in KS B ISO 2768-1				TITLE 1/8" NPT CROSS FTNCS02																											
NOMINAL DIM.(MM)		CLASS OF FINISH		<table border="1"> <tr> <td>APPD BY</td> <td>CHD BY</td> <td>DED BY</td> <td>DRN BY</td> <td>WORK NO.</td> <td>REV. NO.</td> </tr> <tr> <td></td> <td>K.Y.J</td> <td>K.Y.J</td> <td>K.Y.J</td> <td>HI-KYJ-200824-11</td> <td></td> </tr> <tr> <td colspan="3">SCALE</td> <td>DRN DATE</td> <td>DWG NO.</td> <td></td> </tr> <tr> <td colspan="3"></td> <td></td> <td>FTNCS02</td> <td></td> </tr> </table>				APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.		K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200824-11		SCALE			DRN DATE	DWG NO.						FTNCS02	
APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.																										
	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200824-11																											
SCALE			DRN DATE	DWG NO.																											
				FTNCS02																											
OVER	UNDER	TOL.	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 200S,																												
6	30	±0.2	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 50S,																												
30	120	±0.3	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 12.5S,																												
120	315	±0.5	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 3.2S,																												
315	1000	±0.8	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 0.8S,																												
1000	2000	±1.2																													
OVER 2000		±1.5																													