



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTNCS06	15,000	Ø7.1	3/8" NPT	STS 316CW

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
		DESIGN SECTION			

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com				
4	-	-	-	-	EA	-
3	-	-	-	-	EA	-
2	-	-	-	-	EA	-
1	CROSS	3/8" NPT	FTNCS06	STS 316CW	1	EA
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT
	PART CODE					FOR ONE SET
REMARK						
MATERIAL LIST FOR ONE SET						
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT TAPER THREAD FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1				TITLE		
NOMINAL DIM.(MM)		CLASS OF FINISH		3/8" NPT CROSS		
OVER	UNDER	TOL.	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$, 200S,	FTNCS06		
0.5	6	±0.1	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$, 50S,	APPD BY	CHD BY	DED BY
6	30	±0.2	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$, 12.5S,	K.Y.J	K.Y.J	K.Y.J
30	120	±0.3	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$, 3.2S,	DRN BY	WORK NO.	REV. NO.
120	315	±0.5	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$, 0.8S,	K.Y.J	HE-KYJ-200824-08	
315	1000	±0.8		SCALE	DRW DATE	DWG NO.
1000	2000	±1.2				FTNCS06
OVER 2000		±1.5				