

1




**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTNCS12	10,000	Ø22.77	3/4" NPT	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	EA	-	
3	-	-	-	-	EA	-	
2	-	-	-	-	EA	-	
1	CROSS	3/4" NPT	FTNCS12	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE					FOR ONE SET	
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT TAPER THREAD FITTING BLOCK				
General tolerance is given in KS B ISO 2768-1				TITLE 3/4" NPT CROSS FTNCS12			
NOMINAL DIM.(MM)		CLASS OF FINISH		APPROVED BY K.Y.J			
OVER	UNDER	TOL.	√ = √, 200S,	CHD BY K.Y.J			
0.5	6	±0.1	√ = √, 50S,	DED BY K.Y.J			
6	30	±0.2	√ = √, 12.5S,	DRN BY K.Y.J			
30	120	±0.3	√ = √, 3.2S,	WORK NO. HI-KYJ-200824-00			
120	315	±0.5	√ = √, 0.8S,	SCALE			
315	1000	±0.8		DRN DATE			
1000	2000	±1.2		DNG NO. FTNCS12			
OVER 2000		±1.5					

REV. NO.

0