



- SPECIFICATIONS

| Catalog No. | Pressure Rating(PSI) | Orifice Size | Port Type | Material |
|-------------|----------------------|--------------|-----------|-----------|
| FTNES06 | 15,000 | Ø7.1 | 3/8" NPT | STS 316CW |

- Note
1. All dimensions for reference only and subject to change.

| | | | | | |
|---------|--------------|----------------|-------------|-------------|--|
| 0 | FOR APPROVAL | 7 | K.Y.J | | |
| REV No. | DESCRIPTION | DRAWING | REVIEWED BY | APPROVED BY | |
| | | DESIGN SECTION | | | |

| | | | | | | | |
|---|--------------|--|-------------------|------------------------------------|----------|--------|--------|
| Website | | Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com | | | | | |
| 4 | - | - | - | - | - | EA | - |
| 3 | - | - | - | - | - | EA | - |
| 2 | - | - | - | - | - | EA | - |
| 1 | ELBOW | 3/8" NPT | FTNES06 | STS 316CW | 1 | EA | - |
| ITEM | NAME OF PART | SPEC | Catalog No. | MATERIAL | QUANTITY | UNIT | REMARK |
| | PART CODE | DESCRIPTION | | FOR ONE SET | | REMARK | |
| MATERIAL LIST FOR ONE SET | | | | | | | |
| No indication chamfer 0.2~0.4 X 45° | | UNIT: MM | | PROJECT TAPER THREAD FITTING BLOCK | | | |
| General tolerance is given in KS B ISO 2768-1 | | | | TITLE 3/8" NPT ELBOW FTNES06 | | | |
| NORMINAL DIM.(MM) | | CLASS OF FINISH | | APPD BY | | | |
| OVER | UNDER | TOL | √ = √, 200S, ~ | GHD BY | | | |
| 0.5 | 6 | ±0.1 | √ = √, 50S, ∇ | DED BY | | | |
| 6 | 30 | ±0.2 | √ = √, 12.5S, ∇∇ | DRN BY | | | |
| 30 | 120 | ±0.3 | √ = √, 3.2S, ∇∇∇ | WORK NO. | | | |
| 120 | 315 | ±0.5 | √ = √, 0.8S, ∇∇∇∇ | HE-KYJ-200825-10 | | | |
| 315 | 1000 | ±0.8 | | SCALE | | | |
| 1000 | 2000 | ±1.2 | | DRN DATE | | | |
| OVER 2000 | | ±1.5 | | DNG NO. | | | |
| | | | | FTNES06 | | | |
| | | | | HIFLUX ® | | | |

