



- SPECIFICATIONS

| Catalog No. | Pressure Rating(PSI) | Orifice Size | Port Type | Material |
|-------------|----------------------|--------------|-----------|-----------|
| FTNTS02 | 15,000 | Ø2.4 | 1/8" NPT | STS 316CW |

- Note
1. All dimensions for reference only and subject to change.

| | | | | | |
|----------------|--------------|---------|-------------|-------------|--|
| 0 | FOR APPROVAL | 7 | K.Y.J | | |
| REV No. | DESCRIPTION | DRAWING | REVIEWED BY | APPROVED BY | |
| DESIGN SECTION | | | | | |

| | | | | | |
|---|--------------|--|------------------------------------|--------------|------------------|
| Website | | Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com | | | |
| 4 | - | - | - | - | EA |
| 3 | - | - | - | - | EA |
| 2 | - | - | - | - | EA |
| 1 | TEE | 1/8" NPT | FTNTS02 | STS 316CW | 1 EA |
| ITEM | NAME OF PART | SPEC | Catalog No. | MATERIAL | QUANTITY UNIT |
| | PART CODE | | | | FOR ONE SET |
| REMARK | | | | | |
| MATERIAL LIST FOR ONE SET | | | | | |
| No indication chamfer 0.2~0.4 X 45° | | UNIT: MM | PROJECT TAPER THREAD FITTING BLOCK | | |
| General tolerance is given in KS B ISO 2768-1 | | | | TITLE | |
| NOMINAL DIM.(MM) | | CLASS OF FINISH | | 1/8" NPT TEE | |
| OVER | UNDER | TOL. | √ = √, 200S, | FTNTS02 | |
| 0.5 | 6 | ±0.1 | √ = √, 50S, | APPD BY | CHKD BY |
| 6 | 30 | ±0.2 | √ = √, 12.5S, | K.Y.J | K.Y.J |
| 30 | 120 | ±0.3 | √ = √, 3.2S, | DED BY | DRN BY |
| 120 | 315 | ±0.5 | √ = √, 0.8S, | K.Y.J | K.Y.J |
| 315 | 1000 | ±0.8 | | WORK NO. | HE-KYJ-200824-14 |
| 1000 | 2000 | ±1.2 | | SCALE | DRW NO. |
| OVER 2000 | | ±1.5 | | DRN DATE | FTNT802 |
| | | | HIFLUX ® | | |