



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTNTS06	15,000	Ø7.1	3/8" NPT	STS 316CW

- Note  
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
		DESIGN SECTION			

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>					
4	-	-	-	-	EA	-	
3	-	-	-	-	EA	-	
2	-	-	-	-	EA	-	
1	TEE	3/8" NPT	FTNTS06	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION		FOR ONE SET		REMARK	
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2~0.4 X 45°		UNIT: MM		PROJECT TAPER THREAD FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1				TITLE 3/8" NPT TEE			
NORMINAL DIM.(MM)		CLASS OF FINISH		FTNTS06			
OVER	UNDER	TOL	√ = √, 200S, ~	APPD BY			
0.5	6	±0.1	√ = √, 50S, ∇	CHD BY	DED BY	DRN BY	WORK NO.
6	30	±0.2	√ = √, 12.5S, ∇∇	K.Y.J	K.Y.J	K.Y.J	HE-KYJ-200225-11
30	120	±0.3	√ = √, 3.2S, ∇∇∇	SCALE		DRN DATE	DWG NO.
120	315	±0.5	√ = √, 0.8S, ∇∇∇∇	DRN DATE		DWG NO.	FTNTS06
315	1000	±0.8					
1000	2000	±1.2					
OVER 2000		±1.5					