



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTNTS12	10,000	Ø15.7	3/4" NPT	STS 316CW

- Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
4	-	-	-	-	EA	-	
3	-	-	-	-	EA	-	
2	-	-	-	-	EA	-	
1	TEE	3/4" NPT	FTNTS12	STS 316CW	1	EA	
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		

MATERIAL LIST FOR ONE SET

No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT	TAPER THREAD FITTING BLOCK									
General tolerance is given in KS B ISO 2768-1			TITLE										
NOMINAL DIM.(MM)			3/4" NPT TEE FTNTS12										
OVER	UNDER	TOL.	CLASS OF FINISH	APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.				
0.5	6	±0.1	√ = √, 200S, ~	K.Y.J	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-20022-12					
6	30	±0.2	√ = √, 50S, ▽	<table border="1"> <tr> <td>SCALE</td> <td>DRN DATE</td> <td>DWG NO.</td> <td>FTNTS12</td> </tr> </table>						SCALE	DRN DATE	DWG NO.	FTNTS12
SCALE	DRN DATE	DWG NO.	FTNTS12										
30	120	±0.3	√ = √, 12.5S, ▽										
120	315	±0.5	√ = √, 3.2S, ▽										
315	1000	±0.8	√ = √, 0.8S, ▽										
1000	2000	±1.2		HIFLUX ®									
OVER 2000		±1.5											