



**- SPECIFICATIONS**

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTPTS06	15,000	Ø7.1	3/8" PT	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
		DESIGN SECTION			

Website		Main site : <a href="http://www.hiflux.com">http://www.hiflux.com</a> Shopping mall : <a href="http://www.hifluxmall.com">http://www.hifluxmall.com</a>				
4	-	-	-	-	EA	-
3	-	-	-	-	EA	-
2	-	-	-	-	EA	-
1	CROSS	3/8" PT	FTPTS06	STS 316CW	1	EA
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT
	PART CODE		DESCRIPTION		FOR ONE SET	
REMARK						
MATERIAL LIST FOR ONE SET						
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT TAPER THREAD FITTING BLOCK			
General tolerance is given in KS B ISO 2768-1				TITLE 3/8" PT CROSS FTPTS06		
NOMINAL DIM.(MM)		CLASS OF FINISH		APPD BY		
OVER	UNDER	TOL.	$\sqrt{\text{V}}$ = $\sqrt{\text{R}}$ , 200S,	CHD BY	DED BY	DRN BY
0.5	6	±0.1	$\sqrt{\text{W}}$ = $\sqrt{\text{Z}}$ , 50S,	K.Y.J	K.Y.J	K.Y.J
6	30	±0.2	$\sqrt{\text{X}}$ = $\sqrt{\text{Y}}$ , 12.5S,	WORK NO. H-KYJ-200824-17		REV. NO.
30	120	±0.3	$\sqrt{\text{Y}}$ = $\sqrt{\text{X}}$ , 3.2S,	SCALE		
120	315	±0.5	$\sqrt{\text{Z}}$ = $\sqrt{\text{Y}}$ , 0.8S,	DRN DATE		
315	1000	±0.8		DNG NO. FTPT808		
1000	2000	±1.2				
OVER 2000		±1.5				