



- SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	Material
FTPCS12	10,000	Ø23.05	3/4" PT	STS 316CW

- Note

1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	7	K.Y.J		
REV No.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY	
DESIGN SECTION					

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com																													
4	-	-	-	-	EA	-																									
3	-	-	-	-	EA	-																									
2	-	-	-	-	EA	-																									
1	CROSS	3/4" PT	FTPCS12	STS 316CW	1	EA																									
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK																								
	PART CODE				FOR ONE SET																										
MATERIAL LIST FOR ONE SET																															
No indication chamfer 0.2~0.4 X 45°		UNIT: MM	PROJECT TAPER THREAD FITTING BLOCK																												
General tolerance is given in KS B ISO 2768-1				TITLE 3/4" PT CROSS FTPCS12																											
NOMINAL DIM.(MM)		CLASS OF FINISH		<table border="1"> <tr> <td>APPD BY</td> <td>CHD BY</td> <td>DED BY</td> <td>DRN BY</td> <td>WORK NO.</td> <td>REV. NO.</td> </tr> <tr> <td>K.Y.J</td> <td>K.Y.J</td> <td>K.Y.J</td> <td>K.Y.J</td> <td>HI-KYJ-200824-10</td> <td></td> </tr> <tr> <td colspan="3">SCALE</td> <td>DRN DATE</td> <td>DWG NO.</td> <td></td> </tr> <tr> <td colspan="3"></td> <td></td> <td>FTPCS12</td> <td></td> </tr> </table>				APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.	K.Y.J	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200824-10		SCALE			DRN DATE	DWG NO.						FTPCS12	
APPD BY	CHD BY	DED BY	DRN BY	WORK NO.	REV. NO.																										
K.Y.J	K.Y.J	K.Y.J	K.Y.J	HI-KYJ-200824-10																											
SCALE			DRN DATE	DWG NO.																											
				FTPCS12																											
OVER	UNDER	TOL.	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 200S,																												
0.5	6	±0.1	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 50S,																												
6	30	±0.2	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 12.5S,																												
30	120	±0.3	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 3.2S,																												
120	315	±0.5	$\sqrt{\text{R}}$ = $\sqrt{\text{R}}$, 0.8S,																												
315	1000	±0.8																													
1000	2000	±1.2																													
OVER 2000		±1.5																													